

Model 3310

3310 Series Professional 1000A AC Clamp Meters provide many functions for professional AC current and voltage measurements including resistance, capacitance and diode test, etc. With mid-size and tear-drop shaped jaw, it is easy to use in crowded cable areas and other tight places.

**Features**

	3310	3311
Current measurements	AC	AC
Digital display counts	4000	4000
Electronic overload protection	*	*
Continuity buzzer & Diode check	*	*
Data Hold function	*	*
Auto Power Off	*	*
Low battery indication	*	*
Display with backlight	*	*
2.16" (55mm) Clamp jaw opening	*	*

**Specifications**

Function	Max. Range	Basic Accuracy	Max. Resolution	3310	3311
AC Current	1000A	±(2.5%+5d)	100mA	*	*
AC Voltage	1000V	±(1.0%+4d)	0.1mV	*	*
DC Voltage	1000V	±(0.5%+4d)	0.1mV	*	*
Resistance	40MΩ	±(1.0%+2d)	0.1Ω	*	*
Capacitance	40mF	±(3.0%+5d)	0.01nF	*	*
Frequency	10MHz	±(1.2%+2d)	0.001Hz	*	*



EMC & LVD  
EN: 61326  
EN: 61010-1, EN: 61010-02-031



Model 3311

Size(HxWxD): 270mm x 107mm x 50mm  
Weight: 554g

Accessories:  
Test leads, gift box with carrying case, 9V battery.



Model 3313

3312/3313/3315/3316 Series Professional 2000A AC, AC/DC Clamp Meters provide many functions for professional AC, AC/DC measurements including resistance, capacitance and diode test, etc. With mid-size and tear-drop shaped jaw, it is easy to use in crowded cable areas and other tight places.



EMC & LVD  
EN: 61326  
EN: 61010-1, EN: 61010-02-031

**Features**

	3312	3313	3315	3316
Current measurements	AC	AC/DC	AC/DC	AC/DC
True RMS measurements		*	*	*
Digital display counts	4000	4000	4000	4000
Electronic overload protection	*	*	*	*
Continuity buzzer & Diode check	*	*	*	*
Data Hold function	*	*	*	*
Peak Hold	*	*	*	*
DCA Zero function	*	*	*	*
Auto Power Off	*	*	*	*
Low battery indication	*	*	*	*
Display with backlight	*	*	*	*
2.16" (55mm) Clamp jaw opening	*	*	*	*

**Specifications**

Function	Max. Range	Basic Accuracy	Max. Resolution	3312	3313	3315	3316
AC Current	2000A	±(2.5%+5d)	100mA	*	*	*	*
DC Current	2000A	±(2.5%+5d)	100mA	*	*	*	*
AC Voltage	1000V	±(1.0%+4d)	0.1mV	*	*	*	*
DC Voltage	1000V	±(0.5%+4d)	0.1mV	*	*	*	*
Resistance	40MΩ	±(1.0%+2d)	0.1Ω	*	*	*	*
Frequency	10MHz	±(1.2%+2d)	0.001Hz	*	*	*	*



Size(HxWxD): 270mm x 107mm x 50mm  
Weight: 554g

Accessories:  
Test leads, gift box with carrying case, 9V battery.

Model 3315



Model 3312