

HOME

PRODUCTS

PROFILE

TECHNICAL INFORMATION

WHAT'S NEW

CONTACT US



## CLAMP METERS

### New Design Digital Clamp Meter



**MODEL 2017**

- Tear drop shaped jaws for ease of use in crowded cable areas and other tight places.
- Three functions in one unit; AC current, AC voltage, and Resistance.
- Designed to meet internationally proven safety standards such as IEC61010-1, UL3111 and VDE0411.

#### ● Specifications

AC A	200/600A
AC V	200/600V
$\Omega$	200 $\Omega$ buzzer sounds below 30 $\pm$ 20 $\Omega$
Conductor Size	$\varnothing$ 33mm max.
Safety Standard	IEC61010-1 CAT. III 600V IEC61010-2-031, IEC61010-2-032
Frequency Response	45Hz~1kHz
Power Source	6F22(9V) $\times$ 1
Dimensions	208(L) $\times$ 91(W) $\times$ 40(D)mm
Weight	400g approx.

# New Design Digital Clamp Meter (TRUE RMS)



CE

## MODEL 2027

- Tear drop shaped jaws for ease of use in crowded cable areas and other tight places.
- Designed to meet internationally proven safety standards such as IEC61010-1, UL3111 and VDE0411.
- True RMS sensing.

### ● Specifications

AC A	200/600A(True RMS)
AC V	200/600V(True RMS)
$\Omega$	200 $\Omega$ buzzer sounds below 30 $\pm$ 20 $\Omega$
Conductor Size	$\varnothing$ 33mm max.
Safety Standard	IEC61010-1 CAT. III 600V IEC61010-2-031, IEC61010-2-032
Frequency Response	40Hz~1kHz
Power Source	6F22(9V) $\times$ 1
Dimensions	208(L) $\times$ 91(W) $\times$ 40(D)mm
Weight	400g approx.