

**20 A/200 A/1200 A**

**For 3 phase power analyzer DW-6093, DW-6095**

# **1200 A AC CURRENT PROBE**

**Model : CP-1201**

**ISO-9001, CE, IEC1010**



**LUTRON ELECTRONIC**

***The Art of Measurement***

**20 A/200 A/1200 A**  
**For 3 phase power analyzer DW-6093, DW-6095**  
**1200 A AC CURRENT PROBE**

**Model : CP-1201**

**FEATURES**

* Range : 20 A/200 A/1200 A.
* Max. conductor size : 50 mm ( 1.9 inch ) Dia.
* Operation frequency : 50 Hz/60 Hz.
* Optional current probe for DW-6093, DW-6095.
* When change the new probe, the calibration procedures are not necessary to be executed.
* Signal output use the banana plugs, durable and safety.
* Power supply is from the meter (DW-6093, DW-6095 ), battery is not necessary.

Operating Humidity	Less than 80% RH.
Dimension	210 x 64 x 33 mm. ( 8.3 X 2.5 X 1.3 inch ). Cable length : 4 meters ( 13.17 feet ). DC plug size : 5.5 mm x 2.5 mm DIA.
Weight	490 g ( 1.08 LB ).
Accessory Included	Operating manual ..... 1 PC.

**SPECIFICATIONS**

Measurement ranges	20 A/200 A/1200 A, switch selectable
Accuracy	± 1% F.S. * F.S. : Full scale of range. * 50/60 Hz.. * 23 ±5 °C
Frequency range	45 to 400 Hz. * Accuracy tested under 50/60 Hz.
Phase error	< ± 1° * 50/60 Hz..
Minimum load	100 K ohm for specified accuracy.
Enclosure material	UL 94-V0 rated.
Safety	IEC 1010, Categories III 600V.
Power Supply	Power supply is from the meter (DW-6093, DW-6095 ), battery is not necessary. * Power supply voltage from DW-6093, DW-6095 is DC 8V± 1V..
Max. Jaw Open Size	50 mm ( 2.0 inch ) Dia.
Operating Temperature	0°C to 50°C ( 32°F to 122°F ).

**FRONT PANEL DESCRIPTIONS**

